

Características / Modelo	CA58	CA59	CA60	CA61	CA62	CA63	CA64	CA65	CA66	CA67	CA68
Voltaje de entrada	12 VDC										
Voltaje de salida	220 a 240 VAC										
Potencia continua	200 W	150 W	75 W	100 W	150 W	300 W	500 W	1000 W	2000 W	2500 W	3000 W
potencia de pico	400 W	300 W	150 W	200 W	300 W	600 W	1000 W	2000 W	4000 W	5000 W	6000 W
Frecuencia de salida	50 Hz \pm 1%										
Forma de onda de salida	Onda Sinusoidal Modificada										
Consumo sin carga	0.35 A	0.30 A	0.30 A	0.10 A	0.20 A	0.40 A	0.60 A	1.10 A	1.05 A	2.00 A	2 A
Eficiencia	> 85%					> 90%					> 85%
Fusible	25 A x 1 ud	20 A x 1 ud	10 A x 1 ud	20 A x 1 ud	20 A x 1 ud	30 A x 1 ud	30 A x 2 uds	30 A x 4 uds	30 A x 6 uds	30 A x 8 ud	30 A x 12 ud
Peso	265 g	265 g	190 g	450 g	480 g	800 g	1200 g	2500 g	4200 g	4800 g	6000 g
Dimensiones (mm)	58 x 39 x 30	58 x 39 x 30	112 x 57 x 34	135 x 75 x 40	155 x 70 x 40	122 x 114 x 60	190 x 112 x 54	228 x 176 x 79	295 x 232 x 109	395 x 190 x 95	440 x 190 x 95
Conexión	Mechero	Mechero	Mechero	Mechero	Mechero	2 bornes	2 bornes	2 bornes	2 bornes	2 bornes	2 bornes
Enchufe bipolar universal	1	1	1	1	1	0	0	0	0	0	0
Enchufe schucko	0	0	0	0	0	1	1	2	2	2	2
Conector USB A hembra	1	1	1	0	0	1	1	1	1	0	1
Interruptor ON/OFF	SI		NO		SI						

BUY ON
www.cablematic.com